

TANGENT[®]

SUSTAINABLE LUMBER

Care & Cleaning Instructions





GENERAL CLEANING

- Scrub boards with soap and water solution using a soft sponge or plastic-bristled brush.
- You can use a soft-bristled toothbrush to clean spaces that are hard to reach.
- To remove surface dust, just wash furniture with cold, clear water.



DEEP CLEANING

- A pressure washer can be used on the lightest setting to deep clean your furniture.
- It is not recommended to use more than 1,500psi.
- Keep the tip of the pressure washer at least 10-12 inches away from the furniture so it does not damage the lumber.

STAIN CHART

STAIN	RECOMMENDED CLEANING PROCESS
Pencil Marks	Use a mild dish detergent and water to saturate the stain. Rinse clean with water.
Ink/Marker	Use a mild dish detergent and water to saturate the stain. Rinse clean with water. For tougher stains, treat area with a penetrating oil. Wipe off and wash clean with water and a mild dish detergent.
Grease or Oil Stain	Use a mild dish detergent and water to saturate the stain. Rinse clean with water.
Embedded Dirt	Use a mild dish detergent to saturate the area. Scrub with a soft-bristled brush. Rinse clean with water.
Wine	Use a mild dish detergent to saturate the area. Scrub with a soft-bristled brush and rinse clean with water.
Chewing Gum	Coat penetrating oil over the area. Gently pry up on any hard pieces with a plastic putty knife. Utilize a soft brush and acetone solvent to remove any fine debris and clean out any crevasses. Rinse area clean with water.
Bird Droppings	Use a mild dish detergent to saturate the area. Scrub with a soft-bristled brush and rinse clean with water.
Stains and Scuffs	A foam eraser sponge may be used for stubborn marks.
Iron and Rust	For tough iron and rust stains, saturate with a heavy-duty rust remover and scrub with a soft-bristled brush.

Always read and follow the product manufacturers' specific instructions before using any cleaning product. Always wear approved safety glasses, gloves, face shield or goggles when operating cleaning equipment. If using alternative cleaning solutions than those outlined above, it is recommended to test the solution on an inconspicuous area of the lumber to make sure it does not harm the surface. For more information visit tangentmaterials.com.