



Tangent® Materials is a privately held company located in Aurora, IL, within the Chicago metropolitan area. The current leadership at Tangent® has been producing innovative plastic lumber and structural timber products for over 20 years. Founded in 2003, Tangent Technologies is committed to **leading innovation in the plastic lumber industry** through engineering processes and new product development.

Tangent® focuses on delivering quality value propositions with a custom-engineered and tailored solution to meet your unique project specifications. Our sales and marketing teams strategically work to increase customer satisfaction and expand our reach as an industry leader. Tangent® manufactures hundreds of sizes and styles of extrusions, including structural lumber engineered for applications such as fencing and decking, to bridge fender systems and more.

Durable, versatile, low cost, abrasion and chemically resistant plastic material

Tangent PolySheet™ is a high-density sheet and the ideal alternative material for a variety of applications. Available for multiple application types, our durable, all-weather sheet offers unparalleled design versatility compared to traditional lumber. Our extensive CNC capabilities enable us to cut Tangent®'s HDPE sheet into custom parts, streamlining your supply chain and minimizing scrap.


Our sheet resists water, mildew, moisture, insects, and chemicals. Repellent to most surface stains, our high-density sheet is low-maintenance and never requires painting, staining, or waterproofing.



Black



Gray



White

DETAILS

COLOR

Black, Gray, White

SHEET

Finished edges

GRADE

Standard Sheet

TEXTURE / SURFACE

Haircell

SIZES

Thickness: 1/2", 3/4", 1"

Width: 48", 54", 60"

Length: 96", 120"



CONFIDENTLY DURABLE

No rotting, splintering or peeling with materials that stand the test of time.



SUSTAINABLY MADE

Our products won't leach chemicals into our environment.



EASE OF CARE

Impervious to moisture, Tangent materials are truly a low-maintenance product.



MADE IN THE USA

Our products are made in the United States.

Suitability and Limitations

These products have greater impact resistance than wood but conversely less rigidity, and therefore prior to use a thorough design engineering study must be performed to determine the suitability of High Density Sheet in any critical application.

Fabrication is similar to wood and normal woodworking tools can be used. One should be advised that by transforming the product by drilling holes and routing edges the integrity and strength of the part can be altered. Eye protective wear, dusk masks, gloves and normal safety precautions must be used when handling and fabricating the product.

Inherent in High Density Sheet products, you will observe a greater coefficient of thermal expansion than stiffer wood products. Therefore, when designing your application, an accommodation must be made to properly allow for expected expansion and contraction over the length of the product.

Static electricity is a naturally occurring phenomenon to all resin based products. On extremely dry days there is the potential to experience a small static shock if you walk across a High Density Sheet product and touch a conducting surface such as a metal fixture. This is comparable to walking across your carpet and receiving a static shock when you touch the door handle. We do not warranty against static electricity as it is a natural occurring phenomenon and is not a manufacturing defect.

During winter conditions, you might find any surface made from High Density Sheet to be slippery in snow, wet and frost conditions. Unlike most other surfaces, you can easily spread rock salt or calcium chloride to restore decent traction and melt the frost or ice layer with no harmful effect to the High Density Sheet products.

Fabrication Recommendations

Tolerance Information

- ± 5% for gauges 1/4 in. up to 1 in.

Cutting and Sawing

Tangent PolySheet™ High Density Polyethylene (HDPE) Sheet can be cut using full range of saw types. Follow recommendations by tooling manufacturers for 'soft plastics.'

Drilling

Standard twist drills work well. A negatively ground rake angle prevents drill jamming.

Turning

Turn using as low a feed as possible with a large cutting depth. Indexable inserts can help provide a smooth cut.

Milling and Routing

High RPM equipment typically used for metals works well. Feed rates between 10 and 16 per minute are recommended.

Conduct a Pre-production Trial

Without scorching or melting the material.

Hardware

Stainless steel fasteners and hardware recommended as well as screws designed for plastics. Allow for thermal expansion and contraction depending on temperature.

Warranty

Tangent® Materials, the manufacturer of Tangent PolySheet™ High Density Polyethylene (HDPE) Sheet products, offers a limited warranty:

(a) What this Limited Warranty Covers: This Limited Warranty covers substantial defects directly caused by termite and fungal decay as set forth below.

(b) How Long This Limited Warranty Lasts: Subject to the terms and conditions of the Limited Product Warranty, Tangent (hereinafter "Manufacturer," "We" or "Us") warrants to the original consumer ("Consumer" or "You" of Tangent® Materials, ("Products")) that, in normal applications the Products will not rot, splinter, decay or suffer structural damage directly from termites or fungal decay under normal use for a period of (50) years from the date of purchase (the "Warranty Period").

Tangent® Materials does not recommend or approve this product for all end use applications. The appropriate national and local code authorities should be consulted for safety, suitability and applicability for intended use prior to purchasing product. (See full warranty details).

This guideline and summary is intended to provide the distributor, installer and end user with basic guidelines and technical specifications for designing and properly installing the High Density Sheet products. However, the installer and/or purchaser of any High Density Sheet product is solely responsible for interpreting specific job conditions and determining the engineering design and suitability of end use and application of any High Density Sheet product. Adherence to applicable building and safety codes for specific locations and applications of this product are the sole responsibility of the installer and/or purchaser. In no event shall Tangent® Materials, the manufacturer of Tangent PolySheet™ High Density Polyethylene (HDPE) Sheet products, be liable for labor, installation, reinstallation or for any indirect, punitive, exemplary or consequential damages of any kind whatsoever from the provisions of this information.

This revision 1.9 [07/20/26] supersedes all other High Density Sheet technical data sheets.

© 2026 Tangent Technologies, LLC. All rights reserved. TANGENT, Tangent PolyLumber, Tangent PolySheet, Tangent Fencing Systems, TanDeck, and other Tangent-related product names are all trademarks owned by Tangent Technologies, LLC. Any use of these trademarks and materials - including digital content and website - including reproduction, modification, distribution, or republication, without the prior written consent of Tangent Technologies, LLC, is strictly prohibited.

STPS001-090126